



MIR PART NUMBER: 1027

General Information:

Product Description:	M 120/I P0/P6 BLACK COS CONV BELT B120
Features:	Temperature Variation Resistant
Market Segment:	Distribution Centers, General Conveying, Parcel Sorting
Applications:	Decline belt, Incline belt

Belt Construction:



Top Side (Material):	PVC
Top Side (Surface):	Smooth, Adhesive
Top Side (Thickness):	- in - mm
Top Side (Color):	Black
Top Side Shore:	-



Bottom Side (Material):	Polyvinylchloride (PVC) with impregnated PES fabric
Bottom Side (Surface):	Friction surface (impregnated)
Bottom Side (Thickness):	- in - mm
Bottom Side (Color):	Black
Bottom Side Shore:	-

Number of plies:	1
Weft:	-

Technical Belt Data:

Foodgrade (FG):	No
Flame Retardant (FR):	No
Belt Weight:	0.83 lbs/ft ² 4.1 kg/m ²
Belt Thickness:	0.13 in 3.4 mm
Material Between Plies:	-
Pulley Diameter (minimum):	3 in 76.2 mm

Tensile Rating:	- lbs/in
Working Temperature Range:	-10 to 180 °F -23 to 82 °C
Hardness Topside:	-
Force at 1% Elongation (static) / k1% Relaxed:	120 lbs/in 21 N/mm
Back Flexing:	- in - mm
Anti-Static:	No

Joining Method:

Alligator #15

Additional Information:

Clipper #1; Finger splice (Flexproof)

