






## MIR PART NUMBER: 12879

### General Information:

<b>Product Description:</b>	M 80/3 E0/E0 WHITE BB RIBBED CONV BELT
<b>Features:</b>	Great For Dough Release
<b>Market Segment:</b>	-
<b>Applications:</b>	-

### Belt Construction:

					
<b>Top Side (Material):</b>		Spun Polyester			
<b>Top Side (Surface):</b>		Bare Ribbed Fabric			
<b>Top Side (Thickness):</b>		- in		- mm	
<b>Top Side (Color):</b>		White			
<b>Top Side Shore:</b>		0A Shore			
					
<b>Bottom Side (Material):</b>		Spun polyester fabric			
<b>Bottom Side (Surface):</b>		Bare			
<b>Bottom Side (Thickness):</b>		- in		- mm	
<b>Bottom Side (Color):</b>		White			
<b>Bottom Side Shore:</b>		-			
<b>Number of plies:</b>		3			
<b>Weft:</b>		Flexible			

### Technical Belt Data:

<b>Foodgrade (FG):</b>	Yes		<b>Tensile Rating:</b>	- lbs/in	
<b>Flame Retardant (FR):</b>	No		<b>Working Temperature Range:</b>	-22 to 176 °F	-30 to 80 °C
<b>Belt Weight:</b>	0.53 lbs/ft²	2.6 kg/m²	<b>Hardness Topside:</b>	0A Shore	
<b>Belt Thickness:</b>	0.1 in	2.5 mm	<b>Force at 1% Elongation (static) / k1% Relaxed:</b>	45.68 lbs/in	8 N/mm
<b>Material Between Plies:</b>	Spun Polyester Fabric		<b>Back Flexing:</b>	1.97 in	50 mm
<b>Pulley Diameter (minimum):</b>	1.97 in	50 mm	<b>Anti-Static:</b>	No	

### Joining Method:

Endless: Single Finger

### Additional Information:

Belting Solved

24/7

On-Site Service 877 MIR-BELT



mir-belting.com  
mir@mir-belting.com