

MIR PART NUMBER: 2051888


General Information:

Product Description:	EX 10/2 0+05 black M2 AS IR
Features:	Antistatic, Impact Resistant, Low Noise
Market Segment:	General Conveying, Airports
Applications:	Slider Bed, Rollers, Flat

Belt Construction:



Top Side (Material):	PVC (Flexam)
Top Side (Surface):	Smooth, M2 Matte Finish
Top Side (Thickness):	0.02 in 0.5 mm
Top Side (Color):	Black
Top Side Shore:	80A Shore



Bottom Side (Material):	Fabric
Bottom Side (Surface):	Fabric
Bottom Side (Thickness):	- in - mm
Bottom Side (Color):	Natural
Bottom Side Shore:	-

Number of plies:	2
Weft:	Rigid

Technical Belt Data:

Foodgrade (FG):	No
Flame Retardant (FR):	Yes
Belt Weight:	0.76 lbs/ft ² 3.7 kg/m ²
Belt Thickness:	0.14 in 3.5 mm
Material Between Plies:	-
Pulley Diameter (minimum):	2.36 in 60 mm

Tensile Rating:	- lbs/in
Working Temperature Range:	14 to 176 °F -10 to 80 °C
Hardness Topside:	80A Shore
Force at 1% Elongation (static) / k1% Relaxed:	56 lbs/in 9.8 N/mm
Back Flexing:	3.94 in 100 mm
Anti-Static:	Yes

Joining Method:

Finger Splice 80X10

Additional Information:

Mechanical Fasteners

Belting Solved

24/7

On-Site Service 877 MIR-BELT



mir-belting.com
mir@mir-belting.com