

MIR PART NUMBER: 2107

General Inform	nation:	
Product Des	cription:	M 150/2 0/R16 GRAY R/T CONV BELT
Features:		-
Market Segi	ment:	-
Applications	s:	-

Top Side (Material):	SBR	В
Top Side (Surface):	Roughtop	В

Top Side (Material):	SBR	
Top Side (Surface):	Roughtop	
Top Side (Thickness):	- in	- mm
Top Side (Color):	Gray	
Top Side Shore:	-	



Bottom Side (Material):	RFL poly	
Bottom Side (Surface):	Bare	
Bottom Side (Thickness):	- in	- mm
Bottom Side (Color):	Black	
Bottom Side Shore:	-	

Number of plies:	2
Weft:	-

Technical Belt Data:

Belt Construction:

Foodgrade (FG):	No	
Flame Retardant (FR):	No	
Belt Weight:	1.6 lbs/ft ²	7.8 kg/m ²
Belt Thickness:	0.26 +/02 in	6.5 +/3 mm
Material Between Plies:	-	
Pulley Diameter (minimum):	2 in	50.8 mm

Tensile Rating:	- lbs/in	
Working Temperature Range:	-40 to 250 °F	-40 to 121 °C
Hardness Topside:	-	
Force at 1% Elongation (static) / k1% Relaxed:	150 lbs/in	26.25 N/mm
Back Flexing:	2 in	50.8 mm
Anti-Static:	No	

Joining Method:

Additional Information:

