

## MIR PART NUMBER: 4226

### General Information:

<b>Product Description:</b>	M 8/1 0/0 GREEN BB CONV BELT UM240GREEN
<b>Features:</b>	-
<b>Market Segment:</b>	Packaging, Wood, Mechanical, Metal Sheets, Glass Industry, Logistics, Airports, Parcel Handling
<b>Applications:</b>	Conveying On Rollers, Conveying On Skid Bed, Conveying On Skid Bed On Top And Return, Trough Conveying On Skid Bed And On Rollers, Accumulator Belts


### Belt Construction:



<b>Top Side (Material):</b>	NBR impregnated polyester	
<b>Top Side (Surface):</b>	Felt	
<b>Top Side (Thickness):</b>	- in	- mm
<b>Top Side (Color):</b>	Green	
<b>Top Side Shore:</b>	-	



<b>Bottom Side (Material):</b>	-	
<b>Bottom Side (Surface):</b>	Felt	
<b>Bottom Side (Thickness):</b>	- in	- mm
<b>Bottom Side (Color):</b>	Green	
<b>Bottom Side Shore:</b>	-	



<b>Number of plies:</b>	0
<b>Weft:</b>	-

### Technical Belt Data:

<b>Foodgrade (FG):</b>	No		<b>Tensile Rating:</b>	- lbs/in	
<b>Flame Retardant (FR):</b>	No		<b>Working Temperature Range:</b>	14 to 248 °F	-10 to 120 °C
<b>Belt Weight:</b>	0.61 lbs/ft²	3 kg/m²	<b>Hardness Topside:</b>	-	
<b>Belt Thickness:</b>	0.22 in	5.5 mm	<b>Force at 1% Elongation (static) / k1% Relaxed:</b>	57.1 (at 1% elongation) lbs/in	10 (at 1 % elongation) N/mm
<b>Material Between Plies:</b>	-		<b>Back Flexing:</b>	7.87 in	200 mm
<b>Pulley Diameter (minimum):</b>	3.94 in	100 mm	<b>Anti-Static:</b>	No	

### Joining Method:

Skived Joint

### Additional Information:

-

