



MIR PART NUMBER: 11112

General Information:

Product Description:	M 60/2 0/U/0 WHITE CONV BELT
Features:	Foodgrade
Market Segment:	Food
Applications:	Flat, Rollers, Slider Bed, Troughed

Belt Construction:



Top Side (Material):	Polyester	
Top Side (Surface):	Bare	
Top Side (Thickness):	- in	- mm
Top Side (Color):	White	
Top Side Shore:	-	

Bottom Side (Material):	Polyester	
Bottom Side (Surface):	Bare	
Bottom Side (Thickness):	- in	- mm
Bottom Side (Color):	Natural	
Bottom Side Shore:	-	



Number of plies:	2
Weft:	Flexible

Technical Belt Data:

Foodgrade (FG):	Yes	
Flame Retardant (FR):	No	
Belt Weight:	0.33 lbs/ft ²	1.61 kg/m ²
Belt Thickness:	0.07 in	1.7 mm
Tension Layer:	Polyester	
Pulley Diameter (minimum):	0.37 in	9.4 mm

Tensile Rating:	- lbs/in	
Working Temperature Range:	-4 to 176 °F	-20 to 80 °C
Hardness Topside:	-	
Force at 1% Elongation (static) / k1% Relaxed:	34.2 lbs/in	6 N/mm
Back Flexing:	0.37 in	9.4 mm
Anti-Static:	No	

Joining Method:

Hot splicing - FOF

Additional Information:

Mechanical Fasteners

