



MIR PART NUMBER: 11336

General Information:

Product Description:	E 60/2 E0/U2 WHITE MINI R/T CONV BELT
Features:	Foodgrade
Market Segment:	-
Applications:	-

Belt Construction:



Top Side (Material):	PUCON	
Top Side (Surface):	Mini Roughtop	
Top Side (Thickness):	- in	- mm
Top Side (Color):	White	
Top Side Shore:	88A Shore	

Bottom Side (Material):	PUCON	
Bottom Side (Surface):	Impregnated Fabric	
Bottom Side (Thickness):	- in	- mm
Bottom Side (Color):	White	
Bottom Side Shore:	-	



Number of plies:	2
Weft:	Flexible

Technical Belt Data:

Foodgrade (FG):	Yes	
Flame Retardant (FR):	No	
Belt Weight:	0.47 lbs/ft ²	2.3 kg/m ²
Belt Thickness:	0.09 in	2.4 mm
Tension Layer:	-	
Pulley Diameter (minimum):	1.18 in	30 mm

Tensile Rating:	- lbs/in	
Working Temperature Range:	-13 to 194 °F	-25 to 90 °C
Hardness Topside:	88A Shore	
Force at 1% Elongation (static) / k1% Relaxed:	45.68 lbs/in	8 N/mm
Back Flexing:	2.75 in	70 mm
Anti-Static:	No	

Joining Method:

Hot splicing is always preferable. Glueing can only be done when the belt is exposed to normal temperature and the humidity is not excessive

Additional Information:

