

MIR PART NUMBER: 1139

General Information:


Product Description:	M 120/2 R0/R15 TAN DIAMOND TOPCONV BELT
Features:	-
Market Segment:	-
Applications:	-

Belt Construction:



Top Side (Material):	Natural/Synthetic	
Top Side (Surface):	Stepped Diamond (Siped)	
Top Side (Thickness):	- in	- mm
Top Side (Color):	Tan	
Top Side Shore:	-	

Bottom Side (Material):	Polyester	
Bottom Side (Surface):	Bare	
Bottom Side (Thickness):	- in	- mm
Bottom Side (Color):	Brown	
Bottom Side Shore:	-	



Number of plies:	2
Weft:	-

Technical Belt Data:

Foodgrade (FG):	No	
Flame Retardant (FR):	No	
Belt Weight:	1.3 lbs/ft ²	6.34 kg/m ²
Belt Thickness:	0.31 +/- .02 in	7.8 +/- .5 mm
Tension Layer:	-	
Pulley Diameter (minimum):	2.5 in	63.5 mm

Tensile Rating:	- lbs/in	
Working Temperature Range:	-40 to 250 °F	-40 to 121 °C
Hardness Topside:	-	
Force at 1% Elongation (static) / k1% Relaxed:	150 (at 2% elongation) lbs/in	26.25 (at 2% elongation) N/mm
Back Flexing:	- in	- mm
Anti-Static:	No	

Joining Method:

Stepped Angle

Additional Information:

