

## MIR PART NUMBER: 15079

### General Information:


<b>Product Description:</b>	E 60/1 UO/U2 WHITE MATTE COS CONV BELT
<b>Features:</b>	Suitable for Powerturns
<b>Market Segment:</b>	Food Bakery, Food Confectionary
<b>Applications:</b>	Slider Bed, Rollers, Flat

### Belt Construction:



<b>Top Side (Material):</b>	Polyurethane Thermoplastic (TPU)	
<b>Top Side (Surface):</b>	Matte	
<b>Top Side (Thickness):</b>	0.01 in	0.2 mm
<b>Top Side (Color):</b>	White	
<b>Top Side Shore:</b>	85A Shore	

<b>Bottom Side (Material):</b>	Spun Polyester Fabric	
<b>Bottom Side (Surface):</b>	PU Impregnated	
<b>Bottom Side (Thickness):</b>	- in	- mm
<b>Bottom Side (Color):</b>	White	
<b>Bottom Side Shore:</b>	-	



<b>Number of plies:</b>	1
<b>Weft:</b>	Flexible

### Technical Belt Data:

<b>Foodgrade (FG):</b>	Yes	
<b>Flame Retardant (FR):</b>	No	
<b>Belt Weight:</b>	0.18 lbs/ft <sup>2</sup>	0.9 kg/m <sup>2</sup>
<b>Belt Thickness:</b>	0.04 in	0.9 mm
<b>Tension Layer:</b>	Spun Polyester	
<b>Pulley Diameter (minimum):</b>	0.24 in	6 mm

<b>Tensile Rating:</b>	- lbs/in	
<b>Working Temperature Range:</b>	-22 to 212 °F	-30 to 100 °C
<b>Hardness Topside:</b>	85A Shore	
<b>Force at 1% Elongation (static) / k1% Relaxed:</b>	22.84 lbs/in	4 N/mm
<b>Back Flexing:</b>	0.39 in	10 mm
<b>Anti-Static:</b>	No	

### Joining Method:

Finger Splice 80X10

### Additional Information:

Mechanical Fasteners

