



## MIR PART NUMBER: 1595

### General Information:

<b>Product Description:</b>	<b>C 100/4 0/0 WHITE BB CONV BELT</b>
<b>Features:</b>	Food Suitable, Temperature Variation Resistant
<b>Market Segment:</b>	Food Bakery, Dough Production, General Conveying, Food Unwrapped/Open, Glass, Laundry, Paper Converting, Paper Manufacturing, Paper Printing & Finishing
<b>Applications:</b>	

### Belt Construction:



<b>Top Side (Material):</b>	Cotton	
<b>Top Side (Surface):</b>	Untreated	
<b>Top Side (Thickness):</b>	0 in	0 mm
<b>Top Side (Color):</b>	White	
<b>Top Side Shore:</b>	-	

<b>Bottom Side (Material):</b>	Cotton	
<b>Bottom Side (Surface):</b>	Untreated	
<b>Bottom Side (Thickness):</b>	0 in	0 mm
<b>Bottom Side (Color):</b>	White	
<b>Bottom Side Shore:</b>	-	



<b>Number of plies:</b>	4
<b>Weft:</b>	Flexible

### Technical Belt Data:

<b>Foodgrade (FG):</b>	Conforms to FDA per Manufacturer Data Sheet	
<b>Flame Retardant (FR):</b>	No	
<b>Belt Weight:</b>	0.06 lbs/ft <sup>2</sup>	0.3 kg/m <sup>2</sup>
<b>Belt Thickness:</b>	0.19 in	4.76 mm
<b>Tension Layer:</b>	-	
<b>Pulley Diameter (minimum):</b>	3 in	76.2 mm

<b>Tensile Rating:</b>	110 lbs/in	
<b>Working Temperature Range:</b>	-40 to 225 °F	-40 to 107 °C
<b>Hardness Topside:</b>	-	
<b>Force at 1% Elongation (static) / k1% Relaxed:</b>	- lbs/in	- N/mm
<b>Back Flexing:</b>	3 in	76.2 mm
<b>Anti-Static:</b>	No	

### Joining Method:

Mechanical Joining

### Additional Information:

Sewn joint

