



MIR PART NUMBER: 1863012

General Information:

Product Description:	60-10 TFE COATED FIBERGLASS
Features:	Non-stick, FDA Compliant, Low friction, Heat and Cold Resistant
Market Segment:	-
Applications:	Packaging, Food Products, Printing and Textiles, Polymer Processing, Building Products, Chemical Processing, Aerospace, Communications & Military

Belt Construction:



Top Side (Material):	PTFE		Bottom Side (Material):	PTFE	
Top Side (Surface):	Smooth		Bottom Side (Surface):	Smooth	
Top Side (Thickness):	- in	- mm	Bottom Side (Thickness):	- in	- mm
Top Side (Color):	Brown		Bottom Side (Color):	Brown	
Top Side Shore:	-		Bottom Side Shore:	-	



Number of plies:	1
Weft:	Flexible

Technical Belt Data:

Foodgrade (FG):	No		Tensile Rating:	- lbs/in	
Flame Retardant (FR):	No		Working Temperature Range:	-400 to 550 °F	-240 to 288 °C
Belt Weight:	0.1 lbs/ft ²	0.49 kg/m ²	Hardness Topside:	-	
Belt Thickness:	0.01 in	0.25 mm	Force at 1% Elongation (static) / k1% Relaxed:	200 (tensile warp) lbs/in	35 (tensile warp) N/mm
Tension Layer:	-		Back Flexing:	- in	- mm
Pulley Diameter (minimum):	- in	- mm	Anti-Static:	Yes	

Joining Method:

Additional Information:

