



## MIR PART NUMBER: 1893895

### General Information:

<b>Product Description:</b>	<b>P 10 R/R 30 GRAY COARSE COVERS TRANS BELT</b>
<b>Features:</b>	High Grip, Energy Saving, Foodgrade, Quick splice
<b>Market Segment:</b>	Logistics Container & Packaging, Carton & Boxes
<b>Applications:</b>	Boxfolding

### Belt Construction:



<b>Top Side (Material):</b>	XNBR elastomer	
<b>Top Side (Surface):</b>	Rough	
<b>Top Side (Thickness):</b>	- in	- mm
<b>Top Side (Color):</b>	Gray	
<b>Top Side Shore:</b>	-	

<b>Bottom Side (Material):</b>	XNBR Elastomer	
<b>Bottom Side (Surface):</b>	Rough	
<b>Bottom Side (Thickness):</b>	- in	- mm
<b>Bottom Side (Color):</b>	Gray	
<b>Bottom Side Shore:</b>	-	



<b>Number of plies:</b>	1
<b>Weft:</b>	-

### Technical Belt Data:

<b>Foodgrade (FG):</b>	Yes	
<b>Flame Retardant (FR):</b>	No	
<b>Belt Weight:</b>	0.63 lbs/ft <sup>2</sup>	3.1 kg/m <sup>2</sup>
<b>Belt Thickness:</b>	0.12 in	3 mm
<b>Tension Layer:</b>	Polyester Fabric	
<b>Pulley Diameter (minimum):</b>	1.18 in	30 mm

<b>Tensile Rating:</b>	- lbs/in	
<b>Working Temperature Range:</b>	32 to 140 °F	0 to 60 °C
<b>Hardness Topside:</b>	-	
<b>Force at 1% Elongation (static) / k1% Relaxed:</b>	57.1 lbs/in	10 N/mm
<b>Back Flexing:</b>	1.18 in	30 mm
<b>Anti-Static:</b>	Yes	

### Joining Method:

QuickSplice110

### Additional Information:

QuickSplice50

