



## MIR PART NUMBER: 1908068

### General Information:

|                             |   |
|-----------------------------|---|
| <b>Product Description:</b> | PA 6 EL/EL GREEN COARSE COVERS AS TRANS BELT    |
| <b>Features:</b>            | High Grip, Shock Absorbing, Classic splice      |
| <b>Market Segment:</b>      | Logistics Container & Packaging, Carton & Boxes |
| <b>Applications:</b>        | Boxfolding                                      |

### Belt Construction:



|                              |                |      |
|------------------------------|----------------|------|
| <b>Top Side (Material):</b>  | XNBR elastomer |      |
| <b>Top Side (Surface):</b>   | Rough          |      |
| <b>Top Side (Thickness):</b> | - in           | - mm |
| <b>Top Side (Color):</b>     | Green          |      |
| <b>Top Side Shore:</b>       | -              |      |

|                                 |                |      |
|---------------------------------|----------------|------|
| <b>Bottom Side (Material):</b>  | XNBR Elastomer |      |
| <b>Bottom Side (Surface):</b>   | Rough          |      |
| <b>Bottom Side (Thickness):</b> | - in           | - mm |
| <b>Bottom Side (Color):</b>     | Green          |      |
| <b>Bottom Side Shore:</b>       | -              |      |



|                         |   |
|-------------------------|---|
| <b>Number of plies:</b> | 1 |
| <b>Weft:</b>            | - |

### Technical Belt Data:

|                                   |                          |                       |
|-----------------------------------|--------------------------|-----------------------|
| <b>Foodgrade (FG):</b>            | No                       |                       |
| <b>Flame Retardant (FR):</b>      | No                       |                       |
| <b>Belt Weight:</b>               | 1.39 lbs/ft <sup>2</sup> | 6.8 kg/m <sup>2</sup> |
| <b>Belt Thickness:</b>            | 0.24 in                  | 6 mm                  |
| <b>Tension Layer:</b>             | Polyamide Foil           |                       |
| <b>Pulley Diameter (minimum):</b> | 2.36 in                  | 60 mm                 |

|   |              |            |
|---|--------------|------------|
| <b>Tensile Rating:</b>                                | - lbs/in     |            |
| <b>Working Temperature Range:</b>                     | 32 to 176 °F | 0 to 80 °C |
| <b>Hardness Topside:</b>                              | -            |            |
| <b>Force at 1% Elongation (static) / k1% Relaxed:</b> | 34.3 lbs/in  | 6 N/mm     |
| <b>Back Flexing:</b>                                  | 2.36 in      | 60 mm      |
| <b>Anti-Static:</b>                                   | Yes          |            |

### Joining Method:

WedgeSkive75D-2.8+

### Additional Information:

