



## MIR PART NUMBER: 1916280

### General Information:

<b>Product Description:</b>	PA 6 EL/EL 30 GREEN COARSE TOPTRANS BELT
<b>Features:</b>	High Grip, Shock Absorbing, Classic splice
<b>Market Segment:</b>	Logistics Container & Packaging, Carton & Boxes
<b>Applications:</b>	Boxfolding

### Belt Construction:



<b>Top Side (Material):</b>	XNBR elastomer	
<b>Top Side (Surface):</b>	Rough	
<b>Top Side (Thickness):</b>	- in	- mm
<b>Top Side (Color):</b>	Green	
<b>Top Side Shore:</b>	-	

<b>Bottom Side (Material):</b>	XNBR Elastomer	
<b>Bottom Side (Surface):</b>	Rough	
<b>Bottom Side (Thickness):</b>	- in	- mm
<b>Bottom Side (Color):</b>	Green	
<b>Bottom Side Shore:</b>	-	



<b>Number of plies:</b>	1
<b>Weft:</b>	-

### Technical Belt Data:

<b>Foodgrade (FG):</b>	No	
<b>Flame Retardant (FR):</b>	No	
<b>Belt Weight:</b>	0.68 lbs/ft <sup>2</sup>	3.32 kg/m <sup>2</sup>
<b>Belt Thickness:</b>	0.12 in	3 mm
<b>Tension Layer:</b>	Polyamide Foil	
<b>Pulley Diameter (minimum):</b>	1.18 in	30 mm

<b>Tensile Rating:</b>	- lbs/in	
<b>Working Temperature Range:</b>	32 to 176 °F	0 to 80 °C
<b>Hardness Topside:</b>	-	
<b>Force at 1% Elongation (static) / k1% Relaxed:</b>	34.3 lbs/in	6 N/mm
<b>Back Flexing:</b>	1.18 in	30 mm
<b>Anti-Static:</b>	Yes	

### Joining Method:

WedgeSkive75D-2.8+

### Additional Information:

