

MIR PART NUMBER: 1928528

General Information:


Product Description:	E 100/2 U0/U0 BLUE AS FBS CONV BELT
Features:	Antistatic, Low Friction, Oil & Grease Resistant, Foodgrade, Anti-hydrolysis
Market Segment:	-
Applications:	-

Belt Construction:



Top Side (Material):	PU
Top Side (Surface):	Impregnated Fabric
Top Side (Thickness):	0 in 0 mm
Top Side (Color):	Blue
Top Side Shore:	0A Shore

Bottom Side (Material):	PU
Bottom Side (Surface):	Impregnated Fabric
Bottom Side (Thickness):	0 in 0 mm
Bottom Side (Color):	Blue
Bottom Side Shore:	0A Shore



Number of plies:	2
Weft:	Rigid

Technical Belt Data:

Foodgrade (FG):	Yes
Flame Retardant (FR):	No
Belt Weight:	0.2 lbs/ft ² 1 kg/m ²
Belt Thickness:	0.04 in 1 mm
Tension Layer:	PU
Pulley Diameter (minimum):	0.2 in 5 mm

Tensile Rating:	- lbs/in
Working Temperature Range:	-13 to 194 °F -25 to 90 °C
Hardness Topside:	0A Shore
Force at 1% Elongation (static) / k1% Relaxed:	45.68 lbs/in 8 N/mm
Back Flexing:	0.2 in 5 mm
Anti-Static:	Yes

Joining Method:

DS/2 (Splice)

Additional Information:

