



## MIR PART NUMBER: 1932059

### General Information:

<b>Product Description:</b>	E 170/2 0/P20 GREEN COS CONV BELT
<b>Features:</b>	Antistatic, Cut Resistant, Abrasion Resistant, Oil & Grease Resistant
<b>Market Segment:</b>	-
<b>Applications:</b>	Slider Bed, Rollers

### Belt Construction:



<b>Top Side (Material):</b>	PVC	
<b>Top Side (Surface):</b>	Smooth	
<b>Top Side (Thickness):</b>	0.08 in	2 mm
<b>Top Side (Color):</b>	Green	
<b>Top Side Shore:</b>	82A Shore	

<b>Bottom Side (Material):</b>	-	
<b>Bottom Side (Surface):</b>	Fabric	
<b>Bottom Side (Thickness):</b>	0 in	0 mm
<b>Bottom Side (Color):</b>	Natural	
<b>Bottom Side Shore:</b>	0A Shore	



<b>Number of plies:</b>	2
<b>Weft:</b>	Rigid

### Technical Belt Data:

<b>Foodgrade (FG):</b>	No	
<b>Flame Retardant (FR):</b>	No	
<b>Belt Weight:</b>	0.98 lbs/ft <sup>2</sup>	4.8 kg/m <sup>2</sup>
<b>Belt Thickness:</b>	0.16 in	4 mm
<b>Tension Layer:</b>	-	
<b>Pulley Diameter (minimum):</b>	3.15 in	80 mm

<b>Tensile Rating:</b>	- lbs/in	
<b>Working Temperature Range:</b>	23 to 176 °F	-5 to 80 °C
<b>Hardness Topside:</b>	82A Shore	
<b>Force at 1% Elongation (static) / k1% Relaxed:</b>	97.1 lbs/in	17 N/mm
<b>Back Flexing:</b>	3.94 in	100 mm
<b>Anti-Static:</b>	Yes	

### Joining Method:

DS/2 (Recommended)

### Additional Information:

DE, DG

