

## MIR PART NUMBER: 1943740

### General Information:


<b>Product Description:</b>	M 200/I 0/0 GREEN FBS CONV BELT
<b>Features:</b>	Low Coefficient Of Friction For Slider Bed Applications
<b>Market Segment:</b>	-
<b>Applications:</b>	Slider Bed, General Conveying Of Boxes, And Other Light Unit Loads

### Belt Construction:



<b>Top Side (Material):</b>	PVC	
<b>Top Side (Surface):</b>	Friction	
<b>Top Side (Thickness):</b>	- in	- mm
<b>Top Side (Color):</b>	Green	
<b>Top Side Shore:</b>	-	

<b>Bottom Side (Material):</b>	PVC	
<b>Bottom Side (Surface):</b>	Brushed	
<b>Bottom Side (Thickness):</b>	- in	- mm
<b>Bottom Side (Color):</b>	Green	
<b>Bottom Side Shore:</b>	-	



<b>Number of plies:</b>	1
<b>Weft:</b>	-

### Technical Belt Data:

<b>Foodgrade (FG):</b>	No	
<b>Flame Retardant (FR):</b>	No	
<b>Belt Weight:</b>	1 lbs/ft <sup>2</sup>	4.9 kg/m <sup>2</sup>
<b>Belt Thickness:</b>	0.17 in	4.32 mm
<b>Tension Layer:</b>	-	
<b>Pulley Diameter (minimum):</b>	4 in	102 mm

<b>Tensile Rating:</b>	- lbs/in	
<b>Working Temperature Range:</b>	20 to 180 °F	-7 to 82 °C
<b>Hardness Topside:</b>	-	
<b>Force at 1% Elongation (static) / k1% Relaxed:</b>	200 (working load) lbs/in	35 (working load) N/mm
<b>Back Flexing:</b>	- in	- mm
<b>Anti-Static:</b>	No	

### Joining Method:

Finger, Skived Bias, #3HT Clipper, 20 Alligator, 125 Staple

### Additional Information:

