

## MIR PART NUMBER: 1943741

### General Information:


<b>Product Description:</b>	M 150/3 0/0 GREEN BLACK FBS CONV BELT
<b>Features:</b>	Resistant To Edge Wear
<b>Market Segment:</b>	-
<b>Applications:</b>	General Conveying Of Unit Loads Such As Packages, Baggage, Boxes, And Parts

### Belt Construction:



<b>Top Side (Material):</b>	PVC	
<b>Top Side (Surface):</b>	Friction	
<b>Top Side (Thickness):</b>	- in	- mm
<b>Top Side (Color):</b>	Green	
<b>Top Side Shore:</b>	-	

<b>Bottom Side (Material):</b>	PVC	
<b>Bottom Side (Surface):</b>	Brushed	
<b>Bottom Side (Thickness):</b>	- in	- mm
<b>Bottom Side (Color):</b>	Black	
<b>Bottom Side Shore:</b>	-	



<b>Number of plies:</b>	3
<b>Weft:</b>	-

### Technical Belt Data:

<b>Foodgrade (FG):</b>	No	
<b>Flame Retardant (FR):</b>	No	
<b>Belt Weight:</b>	1 lbs/ft <sup>2</sup>	4.9 kg/m <sup>2</sup>
<b>Belt Thickness:</b>	0.15 in	3.86 mm
<b>Tension Layer:</b>	-	
<b>Pulley Diameter (minimum):</b>	2 in	51 mm

<b>Tensile Rating:</b>	- lbs/in	
<b>Working Temperature Range:</b>	20 to 180 °F	-7 to 82 °C
<b>Hardness Topside:</b>	-	
<b>Force at 1% Elongation (static) / k1% Relaxed:</b>	150 (working load) lbs/in	26.25 (working load) N/mm
<b>Back Flexing:</b>	- in	- mm
<b>Anti-Static:</b>	No	

### Joining Method:

FOF Yes, Finger Yes, Bias Stepped Yes, Skived Bias Yes, Clipper UX-1, Alligator 7, Staple 62

### Additional Information:

