



MIR PART NUMBER: 1953496

General Information:

Product Description:	PA 15 R/R 30 BLUE GRAY TRANS BELT
Features:	High Efficient Rubber Cover, Shock Absorbing, Abrasion Resistant, Classic Splice
Market Segment:	Textile, Logistics
Applications:	Roller Drives, Yarn Spinning, Twisting

Belt Construction:



Top Side (Material):	XNBR elastomer	
Top Side (Surface):	Rough	
Top Side (Thickness):	- in	- mm
Top Side (Color):	Blue	
Top Side Shore:	-	

Bottom Side (Material):	XNBR Elastomer	
Bottom Side (Surface):	Rough	
Bottom Side (Thickness):	- in	- mm
Bottom Side (Color):	Gray	
Bottom Side Shore:	-	



Number of plies:	1
Weft:	-

Technical Belt Data:

Foodgrade (FG):	No	
Flame Retardant (FR):	No	
Belt Weight:	0.72 lbs/ft ²	3.5 kg/m ²
Belt Thickness:	0.12 in	3 mm
Tension Layer:	Polyamide Foil	
Pulley Diameter (minimum):	3.15 in	80 mm

Tensile Rating:	- lbs/in	
Working Temperature Range:	32 to 176 °F	0 to 80 °C
Hardness Topside:	-	
Force at 1% Elongation (static) / k1% Relaxed:	85.65 lbs/in	15 N/mm
Back Flexing:	3.15 in	80 mm
Anti-Static:	Yes	

Joining Method:

WedgeSkive75D-2.8+

Additional Information:

