



## MIR PART NUMBER: 1965316

### General Information:


<b>Product Description:</b>	M 220/I R15/R30 BLACK MOR CBS CONV BELT
<b>Features:</b>	Moderate Oil Resistant, 2/220 1/8 x 1/16 MOR
<b>Market Segment:</b>	Wood Chips, Linseed, Cottonseed, Corn Kernels, Whole Soybeans
<b>Applications:</b>	-

### Belt Construction:



<b>Top Side (Material):</b>	MOR	
<b>Top Side (Surface):</b>	Smooth	
<b>Top Side (Thickness):</b>	8-Jan in	3.18 mm
<b>Top Side (Color):</b>	Black	
<b>Top Side Shore:</b>	65A +/- 5 Shore	

<b>Bottom Side (Material):</b>	MOR	
<b>Bottom Side (Surface):</b>	Smooth	
<b>Bottom Side (Thickness):</b>	16-Jan in	1.59 mm
<b>Bottom Side (Color):</b>	Black	
<b>Bottom Side Shore:</b>	-	



<b>Number of plies:</b>	2
<b>Weft:</b>	-

### Technical Belt Data:

<b>Foodgrade (FG):</b>	No	
<b>Flame Retardant (FR):</b>	No	
<b>Belt Weight:</b>	- lbs/ft <sup>2</sup>	- kg/m <sup>2</sup>
<b>Belt Thickness:</b>	0.29 in	7.39 mm
<b>Tension Layer:</b>	MOR	
<b>Pulley Diameter (minimum):</b>	16 in	406.4 mm

<b>Tensile Rating:</b>	220 lbs/in	
<b>Working Temperature Range:</b>	-40 to 250 °F	-40 to 121 °C
<b>Hardness Topside:</b>	65A +/-5 Shore	
<b>Force at 1% Elongation (static) / k1% Relaxed:</b>	220 (working load) lbs/in	38.5 (working load) N/mm
<b>Back Flexing:</b>	- in	- mm
<b>Anti-Static:</b>	No	

### Joining Method:

Vulcanized Step Splice, Mechanical Fasteners

### Additional Information:

