


## MIR PART NUMBER: 1965321

### General Information:


<b>Product Description:</b>	M 330/I R15/R47 BLACK CBS CONVBELT
<b>Features:</b>	3/330 x 3/16 x 1/16 MOR
<b>Market Segment:</b>	-
<b>Applications:</b>	-

### Belt Construction:



<b>Top Side (Material):</b>	MOR	
<b>Top Side (Surface):</b>	Smooth	
<b>Top Side (Thickness):</b>	16-Mar in	4.76 mm
<b>Top Side (Color):</b>	Black	
<b>Top Side Shore:</b>	65A +/- 5 Shore	

<b>Bottom Side (Material):</b>	MOR	
<b>Bottom Side (Surface):</b>	Smooth	
<b>Bottom Side (Thickness):</b>	16-Jan in	1.59 mm
<b>Bottom Side (Color):</b>	Black	
<b>Bottom Side Shore:</b>	-	



<b>Number of plies:</b>	3
<b>Weft:</b>	-

### Technical Belt Data:

<b>Foodgrade (FG):</b>	No	
<b>Flame Retardant (FR):</b>	No	
<b>Belt Weight:</b>	- lbs/ft <sup>2</sup>	- kg/m <sup>2</sup>
<b>Belt Thickness:</b>	0.39 in	10 mm
<b>Tension Layer:</b>	MOR	
<b>Pulley Diameter (minimum):</b>	18 @ 80%-100% Rated Tension in	457.2 @ 80%-100% Rated Tension mm

<b>Tensile Rating:</b>	- lbs/in	
<b>Working Temperature Range:</b>	-40 to 250 °F	-40 to 121 °C
<b>Hardness Topside:</b>	65A +/-5 Shore	
<b>Force at 1% Elongation (static) / k1% Relaxed:</b>	330 (working load) lbs/in	57.75 (working load) N/mm
<b>Back Flexing:</b>	- in	- mm
<b>Anti-Static:</b>	No	

### Joining Method:

Vulcanized Step Splice, Mechanical Fasteners

### Additional Information:

