



MIR PART NUMBER: 1965323

General Information:

Product Description:	M 330/I 0/R47 BLACK MOR COS CONV BELT
Features:	3/330 3/16 x Bare MOR
Market Segment:	-
Applications:	-

Belt Construction:



Top Side (Material):	MOR	
Top Side (Surface):	Smooth	
Top Side (Thickness):	16-Mar in	4.76 mm
Top Side (Color):	Black	
Top Side Shore:	65A +/- 5 Shore	

Bottom Side (Material):	Polyester/Nylon	
Bottom Side (Surface):	Bare	
Bottom Side (Thickness):	- in	- mm
Bottom Side (Color):	Brown	
Bottom Side Shore:	-	



Number of plies:	3
Weft:	-

Technical Belt Data:

Foodgrade (FG):	No	
Flame Retardant (FR):	No	
Belt Weight:	- lbs/ft ²	- kg/m ²
Belt Thickness:	0.33 in	8.33 mm
Tension Layer:	MOR	
Pulley Diameter (minimum):	18 @ 80%-100% Rated Tension in	457.2 @ 80%-100% Rated Tension mm

Tensile Rating:	- lbs/in	
Working Temperature Range:	-40 to 250 °F	-40 to 121 °C
Hardness Topside:	65A +/-5 Shore	
Force at 1% Elongation (static) / k1% Relaxed:	330 (working load) lbs/in	57.75 (working load) N/mm
Back Flexing:	- in	- mm
Anti-Static:	No	

Joining Method:

Vulcanized Step Splice, Mechanical Fasteners

Additional Information:

