



MIR PART NUMBER: 1965325

General Information:

Product Description:	M 220/2 R15/R30 BLACK MAXICLEAT CBS CONV BELT
Features:	2/220 1/8 x 1/16 Grade II V-cleat
Market Segment:	-
Applications:	-

Belt Construction:



Top Side (Material):	Grade 2 SBR	
Top Side (Surface):	Chevron V-Cleats	
Top Side (Thickness):	1/8 (with V-Cleat) in	3.18 (with V-Cleat) mm
Top Side (Color):	Black	
Top Side Shore:	65A +/- 5 Shore	

Bottom Side (Material):	Grade 2 SBR	
Bottom Side (Surface):	Smooth	
Bottom Side (Thickness):	16-Jan in	1.59 mm
Bottom Side (Color):	Black	
Bottom Side Shore:	-	



Number of plies:	2
Weft:	-

Technical Belt Data:

Foodgrade (FG):	No	
Flame Retardant (FR):	No	
Belt Weight:	- lbs/ft ²	- kg/m ²
Belt Thickness:	0.29 (0.54 including cleat) in	7.4 (13.7 including cleat) mm
Tension Layer:	Grade 2 SBR	
Pulley Diameter (minimum):	16 @ 80%-100% Rated Tension in	406.4 @ 80%-100% Rated Tension mm

Tensile Rating:	220 lbs/in	
Working Temperature Range:	-40 to 250 °F	-40 to 121 °C
Hardness Topside:	65A +/-5 Shore	
Force at 1% Elongation (static) / k1% Relaxed:	220 (working load) lbs/in	38.5 (working load) N/mm
Back Flexing:	- in	- mm
Anti-Static:	No	

Joining Method:

Vulcanized Step Splice, Mechanical Fasteners

Additional Information:

