

MIR PART NUMBER: 1965326

General Information:


Product Description:	M 220/2 0/R32 BLACK MOR V-CLEAT COS CONV
Features:	2/220 1/8 x Bare MOR V-Cleat
Market Segment:	-
Applications:	-

Belt Construction:



Top Side (Material):	MOR	
Top Side (Surface):	V-Cleat	
Top Side (Thickness):	8-Jan in	3.18 mm
Top Side (Color):	Black	
Top Side Shore:	60A +/- 5 Shore	

Bottom Side (Material):	Polyester/Nylon	
Bottom Side (Surface):	Bare	
Bottom Side (Thickness):	- in	- mm
Bottom Side (Color):	Brown	
Bottom Side Shore:	-	



Number of plies:	2	
Weft:	-	

Technical Belt Data:

Foodgrade (FG):	No	
Flame Retardant (FR):	No	
Belt Weight:	- lbs/ft ²	- kg/m ²
Belt Thickness:	0.23 in	5.79 mm
Tension Layer:	-	
Pulley Diameter (minimum):	10 in	254 mm

Tensile Rating:	- lbs/in	
Working Temperature Range:	-30 to 225 °F	-34 to 107 °C
Hardness Topside:	60A +/-5 Shore	
Force at 1% Elongation (static) / k1% Relaxed:	220 (working load) lbs/in	38.5 (working load) N/mm
Back Flexing:	8 in	203.2 mm
Anti-Static:	No	

Joining Method:

Lap Splice Mechanical Lacing

Additional Information:

