



## MIR PART NUMBER: 1997190

### General Information:

<b>Product Description:</b>	M 120/I BLACK BB CONV BELT
<b>Features:</b>	High Conductivity
<b>Market Segment:</b>	Logistics Distribution & Warehousing
<b>Applications:</b>	Flat, Rollers, Slider Bed

### Belt Construction:



<b>Top Side (Material):</b>	Felt	
<b>Top Side (Surface):</b>	Felt	
<b>Top Side (Thickness):</b>	- in	- mm
<b>Top Side (Color):</b>	Black	
<b>Top Side Shore:</b>	-	

<b>Bottom Side (Material):</b>	Felt	
<b>Bottom Side (Surface):</b>	Felt	
<b>Bottom Side (Thickness):</b>	- in	- mm
<b>Bottom Side (Color):</b>	Black	
<b>Bottom Side Shore:</b>	-	



<b>Number of plies:</b>	1
<b>Weft:</b>	-

### Technical Belt Data:

<b>Foodgrade (FG):</b>	No	
<b>Flame Retardant (FR):</b>	No	
<b>Belt Weight:</b>	0.25 lbs/ft <sup>2</sup>	1.2 kg/m <sup>2</sup>
<b>Belt Thickness:</b>	0.1 in	2.5 mm
<b>Tension Layer:</b>	-	
<b>Pulley Diameter (minimum):</b>	1.18 in	30 mm

<b>Tensile Rating:</b>	- lbs/in	
<b>Working Temperature Range:</b>	-4 to 248 °F	-20 to 120 °C
<b>Hardness Topside:</b>	-	
<b>Force at 1% Elongation (static) / k1% Relaxed:</b>	- lbs/in	- N/mm
<b>Back Flexing:</b>	2.36 in	60 mm
<b>Anti-Static:</b>	No	

### Joining Method:

Mechanical Fasteners

### Additional Information:

Skive Splice

