



## MIR PART NUMBER: 1999388

### General Information:

<b>Product Description:</b>	E 150/3 0/P30 GREEN COS CONV BELT
<b>Features:</b>	Foodgrade
<b>Market Segment:</b>	Logistics Box, Carton, & Paper
<b>Applications:</b>	Slider Bed, Rollers, Flat

### Belt Construction:



<b>Top Side (Material):</b>	Flexam, PVC	
<b>Top Side (Surface):</b>	Smooth, Glossy	
<b>Top Side (Thickness):</b>	0.14 in	3.6 mm
<b>Top Side (Color):</b>	Petrol, Green	
<b>Top Side Shore:</b>	35A Shore	

<b>Bottom Side (Material):</b>	Polyester	
<b>Bottom Side (Surface):</b>	Bare	
<b>Bottom Side (Thickness):</b>	- in	- mm
<b>Bottom Side (Color):</b>	Natural	
<b>Bottom Side Shore:</b>	-	



<b>Number of plies:</b>	3
<b>Weft:</b>	Rigid

### Technical Belt Data:

<b>Foodgrade (FG):</b>	Yes	
<b>Flame Retardant (FR):</b>	No	
<b>Belt Weight:</b>	1.5 lbs/ft <sup>2</sup>	7.3 kg/m <sup>2</sup>
<b>Belt Thickness:</b>	0.26 in	6.6 mm
<b>Tension Layer:</b>	Polyester	
<b>Pulley Diameter (minimum):</b>	3.15 in	80 mm

<b>Tensile Rating:</b>	- lbs/in	
<b>Working Temperature Range:</b>	5 to 176 °F	-15 to 80 °C
<b>Hardness Topside:</b>	35A Shore	
<b>Force at 1% Elongation (static) / k1% Relaxed:</b>	85.65 lbs/in	15 N/mm
<b>Back Flexing:</b>	3.94 in	100 mm
<b>Anti-Static:</b>	No	

### Joining Method:

Hot splicing - FOF

### Additional Information:

Mechanical Fasteners

