



MIR PART NUMBER: 2006214

General Information:

Product Description:	M 160/I 0/R0 BLACK FXB CONV BELT
Features:	Flame Retardant, High Friction
Market Segment:	Logistics Distribution & Warehousing
Applications:	Loading And Unloading, Telescopic Conveyors, Metering

Belt Construction:



Top Side (Material):	SBR	
Top Side (Surface):	Light Impression	
Top Side (Thickness):	- in	- mm
Top Side (Color):	Black	
Top Side Shore:	58A Shore	

Bottom Side (Material):	Impregnated fabric	
Bottom Side (Surface):	Impregnated Fabric	
Bottom Side (Thickness):	- in	- mm
Bottom Side (Color):	Black	
Bottom Side Shore:	-	



Number of plies:	2
Weft:	Very Rigid

Technical Belt Data:

Foodgrade (FG):	No	
Flame Retardant (FR):	Yes	
Belt Weight:	0.9 lbs/ft ²	4.4 kg/m ²
Belt Thickness:	0.13 in	3.3 mm
Tension Layer:	Polyester/ Polyamide	
Pulley Diameter (minimum):	2 in	50.8 mm

Tensile Rating:	- lbs/in	
Working Temperature Range:	-4 to 176 °F	-20 to 80 °C
Hardness Topside:	58A Shore	
Force at 1% Elongation (static) / k1% Relaxed:	90.22 (at 2% elongation) lbs/in	15.79 (at 2% elongation) N/mm
Back Flexing:	- in	- mm
Anti-Static:	No	

Joining Method:

Mechanical Fasteners

Additional Information:

