



MIR PART NUMBER: 2007930

General Information:

Product Description:	220/I P0/P0 BLACK STATIC CONDCONV BELT
Features:	-
Market Segment:	Logistics, General Conveying
Applications:	-

Belt Construction:



Top Side (Material):	Felt	
Top Side (Surface):	Felt	
Top Side (Thickness):	- in	- mm
Top Side (Color):	Black	
Top Side Shore:	-	

Bottom Side (Material):	Felt	
Bottom Side (Surface):	Felt	
Bottom Side (Thickness):	- in	- mm
Bottom Side (Color):	Black	
Bottom Side Shore:	-	



Number of plies:	0
Weft:	-

Technical Belt Data:

Foodgrade (FG):	No	
Flame Retardant (FR):	No	
Belt Weight:	0.43 +/- .05 lbs/ft ²	2.10 +/- .24 kg/m ²
Belt Thickness:	0.13 +/- .01 in	3.3 +/- .2 mm
Tension Layer:	-	
Pulley Diameter (minimum):	1.97 in	50 mm

Tensile Rating:	- lbs/in	
Working Temperature Range:	10 to 176 °F	-12 to 80 °C
Hardness Topside:	-	
Force at 1% Elongation (static) / k1% Relaxed:	125.6 (at 1.5% elongation) lbs/in	22 (at 1.5% elongation) N/mm
Back Flexing:	2.95 in	75 mm
Anti-Static:	No	

Joining Method:

Skive, Mechanical Fastener

Additional Information:

