



## MIR PART NUMBER: 2015984


### General Information:

<b>Product Description:</b>	RM 25 BLUE DIAMOND BOTTOM
<b>Features:</b>	Chemical Resistant, Wear Resistant Bottom Side
<b>Market Segment:</b>	Food
<b>Applications:</b>	-

### Belt Construction:



<b>Top Side (Material):</b>	TPU-E	<b>Bottom Side (Material):</b>	TPU-E
<b>Top Side (Surface):</b>	Smooth, M1 Fine Matte Finish	<b>Bottom Side (Surface):</b>	Oval
<b>Top Side (Thickness):</b>	- in      - mm	<b>Bottom Side (Thickness):</b>	- in      - mm
<b>Top Side (Color):</b>	Light Blue	<b>Bottom Side (Color):</b>	Light Blue
<b>Top Side Shore:</b>	90A Shore	<b>Bottom Side Shore:</b>	-



<b>Number of plies:</b>	0
<b>Weft:</b>	-

### Technical Belt Data:

<b>Foodgrade (FG):</b>	Yes	<b>Tensile Rating:</b>	- lbs/in
<b>Flame Retardant (FR):</b>	No	<b>Working Temperature Range:</b>	-4 to 158 °F      -20 to 70 °C
<b>Belt Weight:</b>	0.66 lbs/ft <sup>2</sup> 3.2 kg/m <sup>2</sup>	<b>Hardness Topside:</b>	90A Shore
<b>Belt Thickness:</b>	0.1 in      2.5 mm	<b>Force at 1% Elongation (static) / k1% Relaxed:</b>	17.13 lbs/in      3 N/mm
<b>Tension Layer:</b>	-	<b>Back Flexing:</b>	1.57 in      40 mm
<b>Pulley Diameter (minimum):</b>	1.57 in      40 mm	<b>Anti-Static:</b>	No

### Joining Method:

Butt Weld

### Additional Information:

