



MIR PART NUMBER: 2027208

General Information:

Product Description:	M 150/3 N0/0 AMBER FXB CONV BELT
Features:	Antistatic, Flame Retardant
Market Segment:	-
Applications:	Flat, Rollers, Slider Bed, Troughed

Belt Construction:



Top Side (Material):	Fabric, Polyester	
Top Side (Surface):	Bare	
Top Side (Thickness):	- in	- mm
Top Side (Color):	Amber	
Top Side Shore:	-	

Bottom Side (Material):	Fabric, Polyester	
Bottom Side (Surface):	Friction	
Bottom Side (Thickness):	- in	- mm
Bottom Side (Color):	Amber	
Bottom Side Shore:	-	



Number of plies:	3
Weft:	Rigid

Technical Belt Data:

Foodgrade (FG):	No	
Flame Retardant (FR):	No	
Belt Weight:	0.58 lbs/ft ²	2.83 kg/m ²
Belt Thickness:	0.1 in	2.62 mm
Tension Layer:	Polyester	
Pulley Diameter (minimum):	1.97 in	50 mm

Tensile Rating:	- lbs/in	
Working Temperature Range:	-40 to 250 °F	-40 to 121 °C
Hardness Topside:	-	
Force at 1% Elongation (static) / k1% Relaxed:	68.52 lbs/in	12 N/mm
Back Flexing:	1.97 in	50 mm
Anti-Static:	No	

Joining Method:

Mechanical Fasteners

Additional Information:

