


## MIR PART NUMBER: 2051870

### General Information:


<b>Product Description:</b>	PHB F 160/2 LIXBB black FR
<b>Features:</b>	Flame Retardant, High Friction
<b>Market Segment:</b>	Logistics Distribution & Warehousing
<b>Applications:</b>	Curved Conveying, Slider Bed, Rollers, Troughed

### Belt Construction:



<b>Top Side (Material):</b>	SBR	
<b>Top Side (Surface):</b>	Light Impression	
<b>Top Side (Thickness):</b>	- in	- mm
<b>Top Side (Color):</b>	Black	
<b>Top Side Shore:</b>	58A Shore	

<b>Bottom Side (Material):</b>	Impregnated fabric	
<b>Bottom Side (Surface):</b>	Impregnated Fabric	
<b>Bottom Side (Thickness):</b>	- in	- mm
<b>Bottom Side (Color):</b>	Brown	
<b>Bottom Side Shore:</b>	-	



<b>Number of plies:</b>	2
<b>Weft:</b>	Rigid

### Technical Belt Data:

<b>Foodgrade (FG):</b>	No	
<b>Flame Retardant (FR):</b>	Yes	
<b>Belt Weight:</b>	0.94 lbs/ft <sup>2</sup>	4.6 kg/m <sup>2</sup>
<b>Belt Thickness:</b>	0.15 in	3.8 mm
<b>Tension Layer:</b>	Polyester/Polyamide	
<b>Pulley Diameter (minimum):</b>	3.5 in	89 mm

<b>Tensile Rating:</b>	- lbs/in	
<b>Working Temperature Range:</b>	-4 to 176 °F	-20 to 80 °C
<b>Hardness Topside:</b>	58A Shore	
<b>Force at 1% Elongation (static) / k1% Relaxed:</b>	45.68 lbs/in	8 N/mm
<b>Back Flexing:</b>	- in	- mm
<b>Anti-Static:</b>	No	

### Joining Method:

Mechanical Fasteners

### Additional Information:

