



MIR PART NUMBER: 2051906

General Information:

Product Description:	EX 20/3 0+00 black AS FR IR
Features:	Antistatic, Flame Retardant, Impact Resistant, Low Noise
Market Segment:	Logistics Container & Packaging
Applications:	Flat, Rollers, Slider Bed

Belt Construction:



Top Side (Material):	Ropanol, PUR	
Top Side (Surface):	Impregnated Fabric	
Top Side (Thickness):	0 in	0 mm
Top Side (Color):	Black	
Top Side Shore:	-	

Bottom Side (Material):	Polyester	
Bottom Side (Surface):	Bare	
Bottom Side (Thickness):	- in	- mm
Bottom Side (Color):	Natural	
Bottom Side Shore:	-	



Number of plies:	3
Weft:	Rigid

Technical Belt Data:

Foodgrade (FG):	No	
Flame Retardant (FR):	Yes	
Belt Weight:	0.78 lbs/ft ²	3.81 kg/m ²
Belt Thickness:	0.14 in	3.5 mm
Tension Layer:	Polyester	
Pulley Diameter (minimum):	3.35 in	85 mm

Tensile Rating:	- lbs/in	
Working Temperature Range:	5 to 176 °F	-15 to 80 °C
Hardness Topside:	-	
Force at 1% Elongation (static) / k1% Relaxed:	114.2 lbs/in	20 N/mm
Back Flexing:	3.94 in	100 mm
Anti-Static:	Yes	

Joining Method:

Clipper lace, Staple lace, plastic spiral lace

Additional Information:

