



## MIR PART NUMBER: 2063453

### General Information:


<b>Product Description:</b>	<b>E 8/2 E0/U03 BLUE CONV BELT</b>
<b>Features:</b>	Antistatic, Foodgrade, Oil & Fat Resistant
<b>Market Segment:</b>	Food Confectionary & Candy, Food Bakery
<b>Applications:</b>	-

### Belt Construction:



<b>Top Side (Material):</b>	PU	
<b>Top Side (Surface):</b>	Smooth, Matte	
<b>Top Side (Thickness):</b>	0.01 in	0.25 mm
<b>Top Side (Color):</b>	Light Blue	
<b>Top Side Shore:</b>	92A Shore	

<b>Bottom Side (Material):</b>	Fabric	
<b>Bottom Side (Surface):</b>	PU Impregnated	
<b>Bottom Side (Thickness):</b>	0 in	0 mm
<b>Bottom Side (Color):</b>	Fabric	
<b>Bottom Side Shore:</b>	-	



<b>Number of plies:</b>	2
<b>Weft:</b>	Rigid

### Technical Belt Data:

<b>Foodgrade (FG):</b>	Yes	
<b>Flame Retardant (FR):</b>	No	
<b>Belt Weight:</b>	0.29 lbs/ft <sup>2</sup>	1.4 kg/m <sup>2</sup>
<b>Belt Thickness:</b>	0.05 in	1.27 mm
<b>Tension Layer:</b>	-	
<b>Pulley Diameter (minimum):</b>	0.79 in	20 mm

<b>Tensile Rating:</b>	- lbs/in	
<b>Working Temperature Range:</b>	-13 to 194 °F	-25 to 90 °C
<b>Hardness Topside:</b>	92A Shore	
<b>Force at 1% Elongation (static) / k1% Relaxed:</b>	45.68 lbs/in	8 N/mm
<b>Back Flexing:</b>	1.18 in	30 mm
<b>Anti-Static:</b>	Yes	

### Joining Method:

Splice Finger 2 ply - 80 x 10 x 90 Deg

### Additional Information:

Mechanical Fasteners

