



MIR PART NUMBER: 2097711

General Information:

Product Description:	R 40/3 0/R0 BLACK/TAN CONV BEL
Features:	-
Market Segment:	Agriculture, Logistics, Airports
Applications:	Slider Bed, Rollers, Incline/Decline Conveying

Belt Construction:



Top Side (Material):	Natural Rubber	
Top Side (Surface):	Diamond	
Top Side (Thickness):	0.21 in	5.3 mm
Top Side (Color):	Tan	
Top Side Shore:	42A Shore	

Bottom Side (Material):	Polyester Fabric	
Bottom Side (Surface):	Bare	
Bottom Side (Thickness):	- in	- mm
Bottom Side (Color):	Brown	
Bottom Side Shore:	-	



Number of plies:	3
Weft:	Flexible

Technical Belt Data:

Foodgrade (FG):	No	
Flame Retardant (FR):	No	
Belt Weight:	1.54 lbs/ft ²	7.5 kg/m ²
Belt Thickness:	0.36 in	9.14 mm
Tension Layer:	RFL Polyester	
Pulley Diameter (minimum):	3 in	76.2 mm

Tensile Rating:	- lbs/in	
Working Temperature Range:	-40 to 250 °F	-40 to 121 °C
Hardness Topside:	42A Shore	
Force at 1% Elongation (static) / k1% Relaxed:	125.62 lbs/in	22 N/mm
Back Flexing:	- in	- mm
Anti-Static:	No	

Joining Method:

Mechanical Fasteners

Additional Information:

