


## MIR PART NUMBER: 2107

### General Information:


<b>Product Description:</b>	M 150/2 0/R16 GRAY R/T CONV BELT
<b>Features:</b>	-
<b>Market Segment:</b>	Agriculture, Logistics, Airports
<b>Applications:</b>	Slider Bed, Rollers, Incline/Decline Conveying

### Belt Construction:



<b>Top Side (Material):</b>	SBR	
<b>Top Side (Surface):</b>	Roughtop	
<b>Top Side (Thickness):</b>	0.15 in	3.8 mm
<b>Top Side (Color):</b>	Gray	
<b>Top Side Shore:</b>	62A Shore	

<b>Bottom Side (Material):</b>	Polyester Fabric	
<b>Bottom Side (Surface):</b>	Bare	
<b>Bottom Side (Thickness):</b>	- in	- mm
<b>Bottom Side (Color):</b>	Brown	
<b>Bottom Side Shore:</b>	-	



<b>Number of plies:</b>	2
<b>Weft:</b>	Flexible

### Technical Belt Data:

<b>Foodgrade (FG):</b>	No	
<b>Flame Retardant (FR):</b>	No	
<b>Belt Weight:</b>	1.6 lbs/ft <sup>2</sup>	7.8 kg/m <sup>2</sup>
<b>Belt Thickness:</b>	0.26 in	6.5 mm
<b>Tension Layer:</b>	Polyester	
<b>Pulley Diameter (minimum):</b>	1.97 in	50 mm

<b>Tensile Rating:</b>	- lbs/in	
<b>Working Temperature Range:</b>	-40 to 250 °F	-40 to 121 °C
<b>Hardness Topside:</b>	62A Shore	
<b>Force at 1% Elongation (static) / k1% Relaxed:</b>	91.36 lbs/in	16 N/mm
<b>Back Flexing:</b>	3.94 in	100 mm
<b>Anti-Static:</b>	No	

### Joining Method:

### Additional Information:

