

MIR PART NUMBER: 2111945

General Information:


Product Description:	E 9/2 EC0/U0 BLACK CONV BELT
Features:	Antistatic, Low Noise
Market Segment:	Logistics Container & Packaging
Applications:	Slider Bed, Rollers, Flat

Belt Construction:



Top Side (Material):	Ropanol, PUR	
Top Side (Surface):	Impregnated Fabric	
Top Side (Thickness):	0 in	0 mm
Top Side (Color):	Black	
Top Side Shore:	-	

Bottom Side (Material):	Polyester	
Bottom Side (Surface):	Bare Fabric	
Bottom Side (Thickness):	- in	- mm
Bottom Side (Color):	Natural	
Bottom Side Shore:	-	



Number of plies:	2
Weft:	Rigid

Technical Belt Data:

Foodgrade (FG):	No	
Flame Retardant (FR):	Yes	
Belt Weight:	0.31 lbs/ft ²	1.5 kg/m ²
Belt Thickness:	0.06 in	1.6 mm
Tension Layer:	Polyester	
Pulley Diameter (minimum):	0.59 in	15 mm

Tensile Rating:	- lbs/in	
Working Temperature Range:	5 to 176 °F	-15 to 80 °C
Hardness Topside:	-	
Force at 1% Elongation (static) / k1% Relaxed:	57.1 lbs/in	10 N/mm
Back Flexing:	0.79 in	20 mm
Anti-Static:	Yes	

Joining Method:

Business service splice

Additional Information:

Glueing can only be done when the belt is exposed to normal temperature and the humidity is not excessive.

