



## MIR PART NUMBER: 2119

### General Information:

<b>Product Description:</b>	NM 80/4 N0/0 TAN SLIP TOP CONVBELT
<b>Features:</b>	-
<b>Market Segment:</b>	-
<b>Applications:</b>	-

### Belt Construction:



<b>Top Side (Material):</b>	RFL Neoprene	
<b>Top Side (Surface):</b>	Bare	
<b>Top Side (Thickness):</b>	- in	- mm
<b>Top Side (Color):</b>	Amber	
<b>Top Side Shore:</b>	-	

<b>Bottom Side (Material):</b>	-	
<b>Bottom Side (Surface):</b>	Friction	
<b>Bottom Side (Thickness):</b>	- in	- mm
<b>Bottom Side (Color):</b>	Tan	
<b>Bottom Side Shore:</b>	-	



<b>Number of plies:</b>	4
<b>Weft:</b>	-

### Technical Belt Data:

<b>Foodgrade (FG):</b>	No	
<b>Flame Retardant (FR):</b>	No	
<b>Belt Weight:</b>	0.68 lbs/ft <sup>2</sup>	3.32 kg/m <sup>2</sup>
<b>Belt Thickness:</b>	0.11 +/- .01 in	2.69 +/- .25 mm
<b>Tension Layer:</b>	-	
<b>Pulley Diameter (minimum):</b>	2 in	50.8 mm

<b>Tensile Rating:</b>	- lbs/in	
<b>Working Temperature Range:</b>	-20 to 250 °F	-29 to 121 °C
<b>Hardness Topside:</b>	-	
<b>Force at 1% Elongation (static) / k1% Relaxed:</b>	48 (at 2% elongation) lbs/in	8.6 (at 2% elongation) N/mm
<b>Back Flexing:</b>	- in	- mm
<b>Anti-Static:</b>	No	

### Joining Method:

Stepped Angle

### Additional Information:

