

## MIR PART NUMBER: 21852

### General Information:

**Product Description:** M 30 BLUE DUAL DRIVE CONV BELT

**Features:** Hygienic And Homogeneous Characteristics

**Market Segment:** Food, FDA/USDA/Dairy

**Applications:** Positive Drive

### Belt Construction:



**Top Side (Material):** Proprietary TPE/TPU

**Top Side (Surface):** Smooth

**Top Side (Thickness):** - in      - mm

**Top Side (Color):** Blue

**Top Side Shore:** 53D Shore


**Bottom Side (Material):** Proprietary TPE/TPU

**Bottom Side (Surface):** Smooth

**Bottom Side (Thickness):** - in      - mm

**Bottom Side (Color):** Blue

**Bottom Side Shore:** 53D Shore



**Number of plies:** 0

**Weft:** -

### Technical Belt Data:

**Foodgrade (FG):** Yes

**Flame Retardant (FR):** No

**Belt Weight:** 0.85 lbs/ft<sup>2</sup>      4.15 kg/m<sup>2</sup>

**Belt Thickness:** 0.12 in      3 mm

**Tension Layer:** -

**Pulley Diameter (minimum):** 3.25 in      82.55 mm

**Tensile Rating:** - lbs/in

**Working Temperature Range:** -5 to 140 °F      -20 to 60 °C

**Hardness Topside:** 53D Shore

**Force at 1% Elongation (static) / k1% Relaxed:** 33.6 (working load) lbs/in      5.88 (working load) N/mm

**Back Flexing:** 3.94 in      100 mm

**Anti-Static:** No

### Joining Method:

Butt Splice, Thermoplastic Hinge Lace

### Additional Information:

