



MIR PART NUMBER: 2339

General Information:

Product Description:	M 20 TAN CONV BELT
Features:	Cut Resistant, Abrasion Resistant, FDA/USDA
Market Segment:	-
Applications:	-

Belt Construction:



Top Side (Material):	Proprietary TPE/TPU		Bottom Side (Material):	Proprietary TPE/TPU	
Top Side (Surface):	Smooth		Bottom Side (Surface):	Smooth	
Top Side (Thickness):	- in	- mm	Bottom Side (Thickness):	- in	- mm
Top Side (Color):	Beige		Bottom Side (Color):	Beige	
Top Side Shore:	95A Shore/46D Shore		Bottom Side Shore:	95A Shore/46D Shore	



Number of plies:	0
Weft:	-

Technical Belt Data:

Foodgrade (FG):	Yes		Tensile Rating:	- lbs/in	
Flame Retardant (FR):	No		Working Temperature Range:	-20 to 158 °F	-30 to 70 °C
Belt Weight:	- lbs/ft ²	- kg/m ²	Hardness Topside:	95A Shore/46D Shore	
Belt Thickness:	0.08 in	2 mm	Force at 1% Elongation (static) / k1% Relaxed:	6.8 lbs/in	1.19 N/mm
Tension Layer:	-		Back Flexing:	1.18 in	30 mm
Pulley Diameter (minimum):	1.18 in	30 mm	Anti-Static:	No	

Joining Method:

Additional Information:

