


MIR PART NUMBER: 24778

General Information:

Product Description:	M 30 BLUE SUPERDRIVE WITH NEG PYR IMPRESSION CONV BELT
Features:	Foodgrade, Hygienic
Market Segment:	Food Bakery
Applications:	Dough Chunker, Designed for conveyors where fabrications or sidewalls are needed

Belt Construction:



Top Side (Material):	Proprietary TPE/TPU	
Top Side (Surface):	Flat, Diamond Pattern Impression	
Top Side (Thickness):	- in	- mm
Top Side (Color):	Blue	
Top Side Shore:	53D Shore	

Bottom Side (Material):	Proprietary TPE/TPU	
Bottom Side (Surface):	Smooth	
Bottom Side (Thickness):	- in	- mm
Bottom Side (Color):	Blue	
Bottom Side Shore:	53D Shore	



Number of plies:	0
Weft:	-

Technical Belt Data:

Foodgrade (FG):	Yes	
Flame Retardant (FR):	No	
Belt Weight:	0.71 (+0.121 added for each row of teeth) lbs/ft ²	3.50 (+.180 added for each row of teeth) kg/m ²
Belt Thickness:	0.12 in	3 mm
Tension Layer:	-	
Pulley Diameter (minimum):	3.15 in	80 mm

Tensile Rating:	- lbs/in	
Working Temperature Range:	-5 to 158 °F	-20 to 70 °C
Hardness Topside:	53D Shore	
Force at 1% Elongation (static) / k1% Relaxed:	35 (working load) lbs/in	6.25 (working load) N/mm
Back Flexing:	3.94 in	100 mm
Anti-Static:	No	

Joining Method:

Butt Splice

Additional Information:

width < 800 mm = 1 row of teeth, 800 mm < width < 910 mm = 1 row or two rows of teeth, width > 910 mm = 2 rows of teeth

Belting Solved

24/7

On-Site Service 877 MIR-BELT



mir-belting.com
mir@mir-belting.com