



## MIR PART NUMBER: 25260

### General Information:

<b>Product Description:</b>	<b>M 40 DARK GREEN EMBOSSED CONV BELT</b>
<b>Features:</b>	Oil Resistant, Impact Resistant, High Grip
<b>Market Segment:</b>	Ceramics, Glass, Cardboard, Metal, Recycling
<b>Applications:</b>	-

### Belt Construction:



<b>Top Side (Material):</b>	Proprietary TPE/TPU	
<b>Top Side (Surface):</b>	Smooth	
<b>Top Side (Thickness):</b>	- in	- mm
<b>Top Side (Color):</b>	Green	
<b>Top Side Shore:</b>	95A Shore	

<b>Bottom Side (Material):</b>	Proprietary TPE/TPU	
<b>Bottom Side (Surface):</b>	Embossed	
<b>Bottom Side (Thickness):</b>	- in	- mm
<b>Bottom Side (Color):</b>	Green	
<b>Bottom Side Shore:</b>	-	



<b>Number of plies:</b>	0
<b>Weft:</b>	-

### Technical Belt Data:

<b>Foodgrade (FG):</b>	No	
<b>Flame Retardant (FR):</b>	No	
<b>Belt Weight:</b>	- lbs/ft <sup>2</sup>	- kg/m <sup>2</sup>
<b>Belt Thickness:</b>	0.16 in	4 mm
<b>Tension Layer:</b>	-	
<b>Pulley Diameter (minimum):</b>	2.36 in	60 mm

<b>Tensile Rating:</b>	- lbs/in	
<b>Working Temperature Range:</b>	-20 to 158 °F	-30 to 70 °C
<b>Hardness Topside:</b>	95A Shore	
<b>Force at 1% Elongation (static) / k1% Relaxed:</b>	9.2 (pretension of 1%) lbs/in	1.6 (pretension of 1%) N/mm
<b>Back Flexing:</b>	2.36 in	60 mm
<b>Anti-Static:</b>	No	

### Joining Method:

Butt Splice

### Additional Information:

