



## MIR PART NUMBER: 29330

### General Information:

<b>Product Description:</b>	E 24/3 P0/P19 WHITE COS CONV BELT
<b>Features:</b>	Antistatic, Cross Rigid, Foodgrade
<b>Market Segment:</b>	-
<b>Applications:</b>	Depanner

### Belt Construction:



<b>Top Side (Material):</b>	PVC	
<b>Top Side (Surface):</b>	Matte	
<b>Top Side (Thickness):</b>	0.04 in	1 mm
<b>Top Side (Color):</b>	White	
<b>Top Side Shore:</b>	65A Shore	

<b>Bottom Side (Material):</b>	Polyester	
<b>Bottom Side (Surface):</b>	Impregnated Fabric	
<b>Bottom Side (Thickness):</b>	- in	- mm
<b>Bottom Side (Color):</b>	White	
<b>Bottom Side Shore:</b>	-	



<b>Number of plies:</b>	3
<b>Weft:</b>	Rigid

### Technical Belt Data:

<b>Foodgrade (FG):</b>	Yes	
<b>Flame Retardant (FR):</b>	No	
<b>Belt Weight:</b>	1.13 lbs/ft <sup>2</sup>	5.5 kg/m <sup>2</sup>
<b>Belt Thickness:</b>	0.18 in	4.6 mm
<b>Tension Layer:</b>	Polyester Fabric	
<b>Pulley Diameter (minimum):</b>	3.94 in	100 mm

<b>Tensile Rating:</b>	- lbs/in	
<b>Working Temperature Range:</b>	14 to 158 °F	-10 to 70 °C
<b>Hardness Topside:</b>	65A Shore	
<b>Force at 1% Elongation (static) / k1% Relaxed:</b>	68.52 lbs/in	12 N/mm
<b>Back Flexing:</b>	9.84 in	250 mm
<b>Anti-Static:</b>	Yes	

### Joining Method:

Finger over finger, Depanners 3 Ply Bias Lap

### Additional Information:

