


MIR PART NUMBER: 36822

General Information:


Product Description:	E 80/2 U0/S2 BLUE AS COS CONV
Features:	Antistatic, Foodgrade, Nonstick
Market Segment:	Food Dairy, Food Confectionary & Candy
Applications:	Slider Bed, Rollers, Flat

Belt Construction:



Top Side (Material):	Silam, Silicone	
Top Side (Surface):	Smooth, Glossy	
Top Side (Thickness):	0.01 in	0.2 mm
Top Side (Color):	Light Blue	
Top Side Shore:	30A Shore	

Bottom Side (Material):	Ropanol, PUR	
Bottom Side (Surface):	Impregnated Fabric	
Bottom Side (Thickness):	- in	- mm
Bottom Side (Color):	-	
Bottom Side Shore:	-	



Number of plies:	2
Weft:	Rigid

Technical Belt Data:

Foodgrade (FG):	Yes	
Flame Retardant (FR):	No	
Belt Weight:	0.31 lbs/ft ²	1.5 kg/m ²
Belt Thickness:	0.06 in	1.5 mm
Tension Layer:	Polyester	
Pulley Diameter (minimum):	0.79 in	20 mm

Tensile Rating:	- lbs/in	
Working Temperature Range:	5 to 194 °F	-15 to 90 °C
Hardness Topside:	30A Shore	
Force at 1% Elongation (static) / k1% Relaxed:	45.68 lbs/in	8 N/mm
Back Flexing:	0.79 in	20 mm
Anti-Static:	Yes	

Joining Method:

Hot splicing is always preferable

Additional Information:

Glueing can only be done when the belt is exposed to normal temperature and the humidity is not excessive.

