



MIR PART NUMBER: 3922


General Information:

Product Description:	E 6/2 U0/U3 BLUE COS AS FG
Features:	Antistatic, Hydrolysis Resistant, Knife Edge Transfer, Oil & Grease Resistant
Market Segment:	Food Confectionary & Candy, Food Bakery
Applications:	Flat, Rollers, Slider Bed

Belt Construction:



Top Side (Material):	Ultranlyl, TPU	Bottom Side (Material):	Ropanol, PUR
Top Side (Surface):	Smooth, Fine Matte Finish	Bottom Side (Surface):	Impregnated Fabric
Top Side (Thickness):	0.01 in 0.3 mm	Bottom Side (Thickness):	- in - mm
Top Side (Color):	Dark Blue	Bottom Side (Color):	Dark blue
Top Side Shore:	86A Shore	Bottom Side Shore:	-



Number of plies:	2
Weft:	Rigid

Technical Belt Data:

Foodgrade (FG):	Yes	Tensile Rating:	- lbs/in
Flame Retardant (FR):	No	Working Temperature Range:	-13 to 194 °F -25 to 90 °C
Belt Weight:	0.29 lbs/ft ² 1.4 kg/m ²	Hardness Topside:	86A Shore
Belt Thickness:	0.05 in 1.3 mm	Force at 1% Elongation (static) / k1% Relaxed:	34.26 lbs/in 6 N/mm
Tension Layer:	Polyester	Back Flexing:	0.31 in 8 mm
Pulley Diameter (minimum):	0.24 in 6 mm	Anti-Static:	Yes

Joining Method:

Splice Finger 2 ply - 80 x 10 x 90 Deg

Additional Information:

Mechanical Fasteners

