



## MIR PART NUMBER: 44493

### General Information:

<b>Product Description:</b>	<b>ZIP LINK RED LINATEX BELT</b>
<b>Features:</b>	Cold Resistant, Heat Resistant, High Grip
<b>Market Segment:</b>	Paper & Print, Corrugated Board
<b>Applications:</b>	Flat, Troughed, Roller Beds

### Belt Construction:



<b>Top Side (Material):</b>	Natural Rubber, Linatex	
<b>Top Side (Surface):</b>	Smooth	
<b>Top Side (Thickness):</b>	0.13 in	3.18 mm
<b>Top Side (Color):</b>	Red	
<b>Top Side Shore:</b>	40A Shore	

<b>Bottom Side (Material):</b>	SBR	
<b>Bottom Side (Surface):</b>	Friction	
<b>Bottom Side (Thickness):</b>	0 in	0 mm
<b>Bottom Side (Color):</b>	Black	
<b>Bottom Side Shore:</b>	-	



<b>Number of plies:</b>	1
<b>Weft:</b>	Flexible

### Technical Belt Data:

<b>Foodgrade (FG):</b>	No	
<b>Flame Retardant (FR):</b>	No	
<b>Belt Weight:</b>	1.19 lbs/ft <sup>2</sup>	5.8 kg/m <sup>2</sup>
<b>Belt Thickness:</b>	0.2 in	5.08 mm
<b>Tension Layer:</b>	Spiral Polyester	
<b>Pulley Diameter (minimum):</b>	4 in	102 mm

<b>Tensile Rating:</b>	- lbs/in	
<b>Working Temperature Range:</b>	0 to 250 °F	-18 to 121 °C
<b>Hardness Topside:</b>	40A Shore	
<b>Force at 1% Elongation (static) / k1% Relaxed:</b>	57.1 lbs/in	10 N/mm
<b>Back Flexing:</b>	8 in	204 mm
<b>Anti-Static:</b>	No	

### Joining Method:

Ziplink

### Additional Information:

