

MIR PART NUMBER: 49284

General Information:


Product Description:	ZIPLINK BLUE LONGITUDINAL RIB EPDM CONV BELT
Features:	High Grip
Market Segment:	-
Applications:	Inclined Conveying, Declined Conveying

Belt Construction:



Top Side (Material):	EPDM	
Top Side (Surface):	Longitudinal Rib	
Top Side (Thickness):	- in	- mm
Top Side (Color):	Blue	
Top Side Shore:	-	

Bottom Side (Material):	Ziplink	
Bottom Side (Surface):	Bare (Stuffed Ziplink)	
Bottom Side (Thickness):	- in	- mm
Bottom Side (Color):	Black	
Bottom Side Shore:	-	



Number of plies:	1
Weft:	-

Technical Belt Data:

Foodgrade (FG):	No	
Flame Retardant (FR):	No	
Belt Weight:	0.93 lbs/ft ²	4.5 kg/m ²
Belt Thickness:	0.17 +/- .02 in	4.32 +/- .51 mm
Tension Layer:	Polyester	
Pulley Diameter (minimum):	3 in	76.2 mm

Tensile Rating:	- lbs/in	
Working Temperature Range:	-40 to 300 °F	-40 to 149 °C
Hardness Topside:	-	
Force at 1% Elongation (static) / k1% Relaxed:	150 (at 2% elongation) lbs/in	26.8 (at 2% elongation) N/mm
Back Flexing:	- in	- mm
Anti-Static:	No	

Joining Method:

Ziplink

Additional Information:

Belting Solved

24/7

On-Site Service 877 MIR-BELT



mir-belting.com
mir@mir-belting.com