



MIR PART NUMBER: 80262

General Information:


Product Description:	M 225/3 E0/Z12 BLUE R/T CONV BELT
Features:	-
Market Segment:	General Conveying
Applications:	Inclined Conveying, Declined Conveying

Belt Construction:



Top Side (Material):	XNBR	
Top Side (Surface):	Roughtop	
Top Side (Thickness):	- in	- mm
Top Side (Color):	Blue	
Top Side Shore:	-	

Bottom Side (Material):	RFL poly	
Bottom Side (Surface):	Bare	
Bottom Side (Thickness):	- in	- mm
Bottom Side (Color):	Brown	
Bottom Side Shore:	-	



Number of plies:	3
Weft:	-

Technical Belt Data:

Foodgrade (FG):	No	
Flame Retardant (FR):	No	
Belt Weight:	1.5 lbs/ft ²	7.3 kg/m ²
Belt Thickness:	.31 +/- .02 in	7.8 +/- .51 mm
Tension Layer:	-	
Pulley Diameter (minimum):	3 in	76.2 mm

Tensile Rating:	- lbs/in	
Working Temperature Range:	0 to 250 °F	-18 to 121 °C
Hardness Topside:	-	
Force at 1% Elongation (static) / k1% Relaxed:	225 (at 2% elongation) lbs/in	40.3 (at 2% elongation) N/mm
Back Flexing:	- in	- mm
Anti-Static:	No	

Joining Method:

Mechanical Fasteners

Additional Information:

