



## MIR PART NUMBER: 83427

### General Information:

<b>Product Description:</b>	ZIP LINK BLUE SMOOTH CARBOX MATTE COVER X BARE BOTTOM CONV BELT
<b>Features:</b>	-
<b>Market Segment:</b>	Corrugated Box
<b>Applications:</b>	-

### Belt Construction:



<b>Top Side (Material):</b>	Carboxylated NBR	
<b>Top Side (Surface):</b>	Light Matte Finish	
<b>Top Side (Thickness):</b>	0.03 in	0.8 mm
<b>Top Side (Color):</b>	Blue	
<b>Top Side Shore:</b>	-	

<b>Bottom Side (Material):</b>	Ziplink	
<b>Bottom Side (Surface):</b>	Bare	
<b>Bottom Side (Thickness):</b>	- in	- mm
<b>Bottom Side (Color):</b>	White	
<b>Bottom Side Shore:</b>	-	



<b>Number of plies:</b>	1
<b>Weft:</b>	-

### Technical Belt Data:

<b>Foodgrade (FG):</b>	No	
<b>Flame Retardant (FR):</b>	No	
<b>Belt Weight:</b>	0.71 lbs/ft <sup>2</sup>	3.5 kg/m <sup>2</sup>
<b>Belt Thickness:</b>	0.13 +/- .02 in	3.4 +/- .38 mm
<b>Tension Layer:</b>	-	
<b>Pulley Diameter (minimum):</b>	2 in	50.8 mm

<b>Tensile Rating:</b>	- lbs/in	
<b>Working Temperature Range:</b>	0 to 250 °F	-18 to 121 °C
<b>Hardness Topside:</b>	-	
<b>Force at 1% Elongation (static) / k1% Relaxed:</b>	150 (at 2% elongation) lbs/in	26.8 (at 2% elongation) N/mm
<b>Back Flexing:</b>	2 in	50.8 mm
<b>Anti-Static:</b>	No	

### Joining Method:

Ziplink

### Additional Information:

