

## MIR PART NUMBER: 9404028


### General Information:

<b>Product Description:</b>	E 100/2 0/U2 GREEN MATTE COS CONV BELT
<b>Features:</b>	Antistatic, Frayless, Oil & Grease Resistant, Foodgrade
<b>Market Segment:</b>	-
<b>Applications:</b>	-

### Belt Construction:



<b>Top Side (Material):</b>	SPU		<b>Bottom Side (Material):</b>	Fabric	
<b>Top Side (Surface):</b>	Satin Matte Finish		<b>Bottom Side (Surface):</b>	Impregnated Fabric, PU	
<b>Top Side (Thickness):</b>	0.02 in	0.4 mm	<b>Bottom Side (Thickness):</b>	0.004 in	0.1 mm
<b>Top Side (Color):</b>	Petrol		<b>Bottom Side (Color):</b>	Natural	
<b>Top Side Shore:</b>	86A Shore		<b>Bottom Side Shore:</b>	-	



<b>Number of plies:</b>	2
<b>Weft:</b>	Rigid

### Technical Belt Data:

<b>Foodgrade (FG):</b>	Yes		<b>Tensile Rating:</b>	- lbs/in	
<b>Flame Retardant (FR):</b>	No		<b>Working Temperature Range:</b>	-4 to 212 °F	-20 to 100 °C
<b>Belt Weight:</b>	0.36 lbs/ft <sup>2</sup>	1.8 kg/m <sup>2</sup>	<b>Hardness Topside:</b>	86A Shore	
<b>Belt Thickness:</b>	0.07 in	1.7 mm	<b>Force at 1% Elongation (static) / k1% Relaxed:</b>	57.1 lbs/in	10 N/mm
<b>Tension Layer:</b>	Nonfray Polyester		<b>Back Flexing:</b>	1.97 in	50 mm
<b>Pulley Diameter (minimum):</b>	1.18 in	30 mm	<b>Anti-Static:</b>	Yes	

### Joining Method:

Finger Splice

### Additional Information:

