

## MIR PART NUMBER: 9404050

### General Information:


<b>Product Description:</b>	E 100/2 U0/P10 GREEN HARD COVER COS CONV BELT
<b>Features:</b>	Antistatic
<b>Market Segment:</b>	-
<b>Applications:</b>	General Conveying

### Belt Construction:



<b>Top Side (Material):</b>	PVC	
<b>Top Side (Surface):</b>	Glossy	
<b>Top Side (Thickness):</b>	0.04 in	0.9 mm
<b>Top Side (Color):</b>	Dark Green	
<b>Top Side Shore:</b>	90A Shore	

<b>Bottom Side (Material):</b>	Polyester Fabric	
<b>Bottom Side (Surface):</b>	Whisper Weave, Low Noise	
<b>Bottom Side (Thickness):</b>	- in	- mm
<b>Bottom Side (Color):</b>	Natural	
<b>Bottom Side Shore:</b>	-	



<b>Number of plies:</b>	2
<b>Weft:</b>	Rigid

### Technical Belt Data:

<b>Foodgrade (FG):</b>	No	
<b>Flame Retardant (FR):</b>	No	
<b>Belt Weight:</b>	0.61 lbs/ft <sup>2</sup>	3 kg/m <sup>2</sup>
<b>Belt Thickness:</b>	0.1 in	2.5 mm
<b>Tension Layer:</b>	Polyester	
<b>Pulley Diameter (minimum):</b>	1.97 in	50 mm

<b>Tensile Rating:</b>	- lbs/in	
<b>Working Temperature Range:</b>	14 to 176 °F	-10 to 80 °C
<b>Hardness Topside:</b>	90A Shore	
<b>Force at 1% Elongation (static) / k1% Relaxed:</b>	57.1 lbs/in	10 N/mm
<b>Back Flexing:</b>	2.75 in	70 mm
<b>Anti-Static:</b>	Yes	

### Joining Method:

### Additional Information:

